

Informacije o proizvodu (EN)

TESLA inverter klima TT51EX21-1832IA

TESLA



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/tesla-inverter-klima-tt51ex21-1832ia-akcija-cena/>

I FEEL

The remote control can keep track of the temperature at its current location and send the signal to the air conditioner, so it can optimize the room temperature for your maximum comfort.



Self-diagnostic

The air conditioner is able to monitor its operations and identify problematic or faulty parts. If they're found, the system will switch off automatically, while the error code will be displayed on the indoor unit.



Anti-fungus

The air conditioner will start the Anti-fungus feature after exiting cooling and dehumidifying mode. It helps prevent fungi and bacteria from spreading in order to maintain a healthy environment.



Noise-minimizing design

With an optimized operating mechanism, sound insulating materials for compressor, low-noise fan motor and ventilation structure that combines modern technology with aerodynamic design, this AC model minimizes noise levels while creating your perfect room temperature.



Turbo mode

When the air conditioner goes into Turbo mode, it will maximize its cooling or heating capacity, making the room cooler or warmer rapidly.



Auto cleaning

When this feature is activated, the indoor unit starts operating in cooling mode with a low fan speed, while the condensed water cleans dust from the evaporator fins. The AC then switches to heating with low fan speed, drying the inside of the indoor unit. Finally, it turns to fan-only mode and blows away the rest of the moisture. The whole process keeps the indoor unit dry and prevents bacterial growth.



Features

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer

| | | | |
|--|---|-----------------------|--|
| Capacity | | | 18000BTU |
| Rated volt and frequency | | V/Hz | 220-240V~/50HZ |
| Mode | | | Cooling Heating |
| Rated capacity | | W | 5100(1250-5900) 5100(1250-6070) |
| Power input | | W | 1580 1374 |
| Current input | | A | 8,10 7,00 |
| SEER-SCOP/ Energy Class | | W/W | 6,1 A++ 4 A+ |
| Operating range | | (°C) | 0 - 53°C -20°C - 30°C |
| Energy consumption (per year, based on standard test results) | | kwh | 293 1330 |
| Dehumidifying | | Kg/h | 1,8 |
| Degree of protection (IN) / (OUT) | | (IP) | IPX4/IPX4 |
| Class of electric protection (IN) / (OUT) | | Class I / Class II | I/I |
| Max. input consumption | | W | 2520 |
| Max. current | | A | 13 |
| Compressor | Model | | KSN98D32UEZ |
| | Type | | Rotary |
| | Brand | | SANYO |
| Indoor | Fan motor | Model | 1170030067G |
| | | Power input | W 20W output |
| | | Capacity | uF 2 |
| | | Indoor Fan Speed RPM | r/min ≤1320 |
| | Indoor fan | Dia. / Length | mm φ92×578 |
| | Indoor Air Circulation | m³/h | 800 |
| | Indoor Noise Level dB | dB(A) | 50/47/43/36 |
| | Net Dimension (L×W×H) | mm | 910×294×195 |
| | Packing Dimension (L×W×H) | mm | 979×372×277 |
| | Net Weight/Gross Weight | Kg | 11/13 |
| Outdoor | Fan motor | Model | 1170040162AB |
| | | Power input | W 33W output |
| | | Capacity | uF / |
| | | Outdoor Fan Speed RPM | r/min ≤1000 |
| | Outdoor fan | Length | mm φ384×134 |
| | Outdoor Noise Level dB | dB(A) | 55 |
| | Net Dimension (L×W×H) | mm | 853×602×349 |
| | Packing Dimension (L×W×H) | mm | 890×628×385 |
| | Net Weight/Gross Weight | Kg | 35/38 |
| | Refrigerant type/weight | g | R32/1.00kg |
| Refrigerant piping | Liquid side / Gas side | mm | 6.35/9.52 |
| | Max. refrigerant pipe length / Max. difference in level | m | 25/10 |

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Tesla, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/tesla-inverter-klima-tt51ex21-1832ia-akcija-cena/>