tehnotzka

https://tehnoteka.rs

Informacije o proizvodu (EN)

HP SSD 1TB FX900



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

https://tehnoteka.rs/p/hp-ssd-1tb-fx900-akcija-cena/



FX900 Pro PCle 4.0 SSD

FX900 Pro M.2 SSD is a PCIe 4.0 high-speed SSD, a new generation enabling superior performance. With a high-performance 8-channel Gen 4 x4 controller and advanced NVMe 1.4 protocol, FX900 Pro achieves up to 7400 MB/s read speed-- that's 2.1X faster than PCIe 3.0 SSD and 13.2X faster than SATA SSD. The independent DRAM cache and ultra-low data delay make it ideal for gamers and professionals seeking ultimate experiences.

8-Channel host controller Independent DDR4 cache Advanced NVMe technology Up to 4 TB capacity Graphene thermal pad

1900 P10 N.2. 21

5-year limited warranty

Product Features

> Supreme speed of 7400 MB/s read and 6700 MB/s write

Designed for high performance and gaming, FX900 Pro uses 8-channel Gen 4 x4 controller, supports NVMe 1.4 technology, and takes the sequential read/ write speeds up to 7400 MB/s and 6700 MB/s. It breaks through the performance bottleneck of previous PCIe generations to upgrade the computing experience for gamers, professionals, and video makers.

> Store more and play more with up to 4 TB capacity

With capacity choices of 512 GB / 1 TB / 2 TB / 4 TB, HP FX900 Pro SSD gives you the space to store your favorite games, design, 4K HD photos, videos and large files. You'll still have room for the next big title.

> Dynamic SLC caching and DRAM cache buffer

Equipped with DRAM independent cache, FX900 Pro greatly improves 4K random read and write performance and reduces SSD access delay. It also supports NCQ (Native Command Queuing) and TRIM command for multi-tasking performance with a continuously fast speed.

> Graphene thermal pad for efficient heat dissipation

Using graphene foam with high thermal conductivity, the working temperature is effectively reduced by about 18 °C. This heat dissipation design is able to reliably reduce performance fluctuations and ensures the fast speed and stable operation of SSD.

> Master 3A games, be fully loaded in seconds

Now you can easily boot up a large AAA game, load a map, and switch scenes on synchronous multiplayer games with pro level performance. Combining remarkable read and write speed with ultra-low data delay, FX900 Pro allows you to load and play games as soon as you're ready.

> Enjoy HP's worry-free customer service

Comes with 5-year limited warranty and free technical support.

HP Advantage

HP, the world's leading IT company, the world's top 500, business covers IT infrastructure equipment, storage, commercial and home computers, printers, digital imaging and other fields, PC shipments for many years in the world's top, the world's billion industry elite are using. HP continues to forge ahead in storage technology and make every effort to create new storage products, and will continue to be committed to providing high-quality, reliable storage products and services to consumers around the world. HP has a comprehensive after-sales system and service outlets in the global region to provide users with a full range of after-sales services.

FX900 Pro M.2 SSD Product Specifications

Interface	PCIe Gen4x4			
Form Factor	M.2 2280			
Capacity	512 GB	1 TB	2 TB	4 TB
DRAM Cache	1 GB	1 GB	2 GB	4 GB
Max. Sequential Reading Speed (MB/s)	7400	7400	7400	7400
Max. Sequential Writing Speed (MB/s)	3800	6400	6700	6700
Random Read Speed (IOPS)	540 K	1014 K	1344 K	1350 K
Random Write Speed (IOPS)	938 K	1079 K	1122 K	1150 K
Dimensions	80 x 22 x 3.2 mm			
Weight	≤ 10 g			
MTBF	> 1,000,000 hours			
Storage Temperature	-40 °C - 85 °C			
Working Temperature	0 °C - 70 °C			
Vibration Resistance	3.1 GRMS (2-500 Hz)			
Shock Resistance	100 G / 6 s			
Certifications	CE, FCC, RoHS, cTUVus, KCC, BSMI, VCCI, RCM			
Limited Warranty	5-Year / 300 TBW	5-Year / 600 TBW	5-Year / 1200 TBW	5-Year / 2400 TBW

1. Updates are required throughout product life cycle when necessary. HP reserves the right to change product images and specifications at any time without notice.

2. All product specifications are under internal test results and are subject to variations by user's system configuration.

3. Not all products are sold in all regions of the world.

4. As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabytes (MB) = 1,048,576 bytes. As used for transfer (GB/s) = one billion bytes per second (MB/s) = one million bytes per second, and gigabyte per second (GB/s) = one billion bytes per second. The maximum valid value for the SATA 6GB/s transfer rate is calculated based on the serial ATA specification published by the SATA-IO organization prior to the date of publication of this specification. For more information, please visit www.sata-io.org.

5. Measured using the MobileMark[™] 2012 benchmark with DIPM (Device Induced Power Management) enabled.

6. MTBF = Mean Time Between Failures based on internal testing using Telcordia stress test.

es are required throughout product life cycle when necessary. HP rese time without notice.

at any time without notice. All product specifications are under internal test results and are subject to variations by user's system configuration. Product are subject to regional availability. Instructions for purchasing high-frequency memory overdoking memory needs to be equipped with a matching motherboard and protectors to exert its overdoking performance. Heate everly prior to purchase whether your matherboard and arQ support the specifications of high your over to boy. Alternal body atter installance to regive the overdoking specific septimation and your over to boy. Alternal body atter installance to regive the overdoking specifications.

tehnotzka

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda hp, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanesenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

https://tehnoteka.rs/p/hp-ssd-1tb-fx900-akcija-cena/