

## Informacije o proizvodu (EN)

CHIEFTEC napajanje PPS-1050FC 1050W



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/chiefttec-napajanje-pps-1050fc-1050w-akcija-cena/>

- 80 PLUS® Gold certified efficiency
- Fully modular cable management
- LLC Half-bridge converter with DC-to-DC technology

The Polaris Series brings CHIEFTEC's trusted and proven experience with high quality, 80 PLUS® Gold certified, fully modular power supplies back to the forefront of modern technology. Polaris Series PSU's feature state-of-the-art technical design including LLC half-bridge converter with DC-to-DC technology, as well as high power-density to allow higher efficiency and power output with a more compact size. Cable lengths of 650mm ensure that these power-supplies can be used even in large builds.



#### Technical data






Model	Polaris Series
Articel no.	PPS-1050FC
ATX12V Version	v 2.53
Efficiency	80 PLUS® Gold
PFC	Active PFC
Fan	135mm FDB silent fan
Dimension (DxWxH)	160mm x 150mm x 86mm
Security	AFC (Automatic Fan speed Control) OCP (Over Current Protection) OPP (Over Power Protection) OTP (Over Temperature Protection) OVP (Over Voltage Protection) SCP (Short Circuit Protection) SIP (Surge & Inrush Protection) UVP (Under Voltage Protection)
Warranty	24 Months

#### Output data

PPS - 1050FC	AC Input	100-240V / 15 - 8A / 50 - 60Hz				
	DC Output	+3.3V	+5V	+12V	-12V	+5VSB
	Max. Current	22A	22A	87.5A	0.3A	3.0A
	Max. Combined Power	120W		1050W	3.6W	15W
			1050W			

\* The listed specifications may be altered at any point in time without any pre-notice.

\*\* Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

	Cable	Connectors	Length (mm)
	24 PIN ATX	1	650
	8 PIN EPS (4+4)	2	2 x 650
	8 PIN PCIe (6+2)	6	3 x 600/100
	SATA	12	3 x 550/100/100/100
	MOLEX	4	550/100/100/100

### Certification



Version: 10/2020

\* The listed specifications may be altered at any point in time without any pre-notice.

\*\* Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Chieftec, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/chieftec-napajanje-pps-1050fc-1050w-akcija-cena/>