

Informacije o proizvodu (EN)

APC BX1200MI-GR uređaj

The APC logo is displayed in a bold, red, sans-serif font. The letters 'A', 'P', and 'C' are connected, with a small trademark symbol (TM) to the upper right of the 'C'.

Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/apc-bx1200mi-gr-uredjaj-akcija-cena/>

Product datasheet

Specifications



APC Back-UPS, 1200VA, Tower, 230V, 4x CEE 7/7 Schuko outlets, AVR

BX1200MI-GR

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Rated Power In W	650 W
Rated Power In Va	1200 VA
Product Or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	Schuko CEE 7/7P
Output Connection Type	4 Schuko
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Battery Voltage	12 V
Battery Capacity	9.0 Ah
Battery Life	3...5 year(s)
Replacement Battery	APCRBC175
Battery Graph Comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended Runtime	0

General

Provided Equipment	user manual
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0

Redundant	No
-----------	----

Physical

Colour	Black
--------	-------

Height	19 cm
--------	-------

Width	14 cm
-------	-------

Depth	39 cm
-------	-------

Net Weight	7.6 kg
------------	--------

Mounting Preference	No preference
---------------------	---------------

Mounting Mode	Not rack-mountable
---------------	--------------------

Two Post Mountable	0
--------------------	---

Usb Compatible	No
----------------	----

Input

Network Frequency	50/60 Hz +/- 5 Hz auto-sensing
-------------------	--------------------------------

Input Voltage Limits	140...300 V
----------------------	-------------

Input Power Factor At Full Load	0.54
---------------------------------	------

Output

Maximum Configurable Power In W	650 W
---------------------------------	-------

Output Frequency	50/60 Hz +/- 1 Hz sync to mains
------------------	---------------------------------

Ups Type	Line interactive
----------	------------------

Wave Type	Stepped approximation to a sinewave
-----------	-------------------------------------

Full Load Runtime	00:01:00 650 W
-------------------	----------------

Half Load Runtime	00:05:00 300 W
-------------------	----------------

Maximum Configurable Power In Va	1200 VA
----------------------------------	---------

Transfer Time	6 ms typical : 10 ms maximum
---------------	------------------------------

Conformance

Product Certifications	CE CB EAC
------------------------	-----------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Equipment Protection Policy	Lifetime : 50000 euros
-----------------------------	------------------------

Environmental

Ambient Air Temperature For Operation	0...40 °C
---------------------------------------	-----------

Relative Humidity	0...95 % non-condensing
-------------------	-------------------------

Operating Altitude	0...3000 m
--------------------	------------

Ambient Air Temperature For Storage	-15...40 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

Storage Altitude	0...3000 m
------------------	------------

Acoustic Level	40 dBA
----------------	--------

Ip Degree Of Protection	IP20
-------------------------	------

Communications & Management

Control Panel	LED Status display with on line : on battery
---------------	--

Surge Protection and Filtering

Surge Energy Rate	273 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	29.7 cm
------------------	---------

Package 1 Width	49.5 cm
-----------------	---------

Package 1 Length	23.5 cm
------------------	---------

Package 1 Weight	8.6 kg
------------------	--------

Scc14	10731304410864
-------	----------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

- Reach Free Of Svhc

- Toxic Heavy Metal Free

- Mercury Free

- Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda APC, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/apc-bx1200mi-gr-uredjaj-akcija-cena/>