

## Informacije o proizvodu (EN)

DELTA Amplon RT 1K UPS uređaj



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/delta-amplon-rt-1k-ups-uredjaj-akcija-cena/>

The power behind competitiveness

# Delta UPS - Amplon Family

RT Series, Single Phase  
1/2/3 kVA

## Reliable power with greater energy-saving features

The Amplon RT 1-3kVA series is an online double-conversion UPS providing consistent sine-wave power to your critical equipment. It supports personal computers, networks, servers, VoIP and telecommunications. The Amplon RT 1-3kVA series features an output power factor of 0.9 and best-in-class AC-AC efficiency up to 94% resulting in greater energy savings. Optional external battery pack can be connected for longer backup time to keep your applications safe and running smoothly at all times.

### Availability

- True online double-conversion topology and zero transfer time to battery ensure high reliability
- Watch-dog design of DSP (Digital Signal Processor) increases reliability
- Cold-start capability provides temporary battery power when the utility power is out
- Fan failure detection alerts users to failed fans
- Hot swappable batteries ensure continuous operation even when batteries are being replaced
- Optional external battery pack for easy scaling of longer backup time
- Operation temperature tolerance up to 50°C ensures critical loads' continuity



### Green & Low TCO

- High output power factor 0.9 provides more real power to critical loads
- High input power factor (pf > 0.99) and low harmonic distortion (iTHD < 5%) save upstream investment
- Up to 94% AC-AC efficiency and 97% efficiency in ECO mode result in marked energy cost savings
- Wide input voltage range reduces the chance of using the battery and extends battery life
- Intelligent battery management sustains battery life and performance
- Fan speed control by load level maximizes efficiency and reduces audible noise

### Flexibility

- Load segment control allows less-critical loads to be disconnected during blackouts and saves battery runtime for important loads
- Convertible rack and tower configuration in 2U size cabinet
- Excellent local communications through rotatable LCD display
- Intelligent management software connectivity via RS232 or USB port



Server



Telecom



Industrial



Network



VoIP



Storage



Medical



# Delta UPS - Amplon Family

RT Series, Single Phase  
1/2/3 kVA

Technical Specifications		RT-1K	RT-2K	RT-3K
Model		RT-1K	RT-2K	RT-3K
Power Rating		1kVA/0.9kW	2kVA/1.8kW	3kVA/2.7kW
Input	Nominal Voltage	200*/208*/220/230/240Vac		
	Voltage range	175~280Vac (full load); 120~175Vac (70~100% load)		
	Frequency	40~70Hz		
	Power Factor	> 0.99 (full load)		
	Current Harmonic Distortion	< 5%		
Output	Power Factor	0.9		
	Voltage	200*/208*/220/230/240Vac		
	Voltage Regulation	± 1% (linear load)		
	Frequency	50/60Hz ± 0.05Hz		
	Voltage Harmonic Distortion	< 2% (linear load)		
	Overload Capability	< 105%: Continuous; 105~125%: 1 minute; 125~150%: 15 seconds		
	Receptacle	IEC C13 x 6	IEC C13 x 6, IEC C19 x 1	
Efficiency	AC-AC	90%	Up to 94%	
	ECO Mode	96%	Up to 97%	
Battery	Battery Voltage	24Vdc	48Vdc	72Vdc
	Typical Backup Time**	6.5 minutes	7 minutes	
	Charge Current	1.5A	2A	
	Recharge Time	3 hours to 90%		
Audible Noise		< 40dB	< 43dB	< 46dB
Display		LCD display and LED indicators		
Interfaces		SMART Slot x 1, RS-232 Port x 1, USB Port x 1, REPO x 1		
Conformance		CE, TISI, RCM, EAC		
Dimensions (W x D x H)	UPS	440 x 335 x 89mm	440 x 432 x 89mm	440 x 610 x 89mm
	External Battery Pack	440 x 335 x 89mm	440 x 432 x 89mm	440 x 610 x 89mm
Weight	UPS	12kg	18kg	28kg
	External Battery Pack	15kg	27kg	44kg
Environment	Operating Temperature	0~50°C***		
	Relative Humidity	5~95% (non-condensing)		

\* When the UPS is de-rated to 90% of its capacity.

\*\* When the total load reaches 75%.

\*\*\* 40~50°C with 80% de-rating.

All specifications are subject to change without prior notice.



Delta's Manufacturing System is Certified by ISO 9001 and ISO 14001 Standards



IACQ Certificate of Hazardous Substance Process Management



Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda DELTA, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/delta-amplon-rt-1k-ups-uredjaj-akcija-cena/>