

## Informacije o proizvodu (EN)

FSP FP 800 UPS uređaj



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/fsp-fp-800-ups-uredjaj-akcija-cena/>

# Line Interactive | FP

## 600/800/1000/1500/2000

### Features

- Compact size
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function
- Generator compatible (option)



MODEL	FP 600	FP 800	FP 1K	FP 1.5K	FP 2K
<b>CAPACITY</b>	600VA / 360W	800VA / 480W	1000VA / 600W	1500VA / 900W	2000VA / 1200W
<b>INPUT</b>					
Voltage	110 / 120Vac or 220 / 230 / 240Vac				
Voltage Range	81-145Vac / 162-290Vac				
Frequency Range	60 / 50Hz (auto sensing)				
<b>OUTPUT</b>					
Voltage	110 / 120Vac or 220 / 230 / 240Vac				
AC Voltage Regulation (Batt. Mode)	±10%				
Frequency Range (Batt. Mode)	60Hz or 50Hz ±1 Hz				
Transfer Time	Typical 2-6 ms				
Waveform (Batt. Mode)	Simulated Sinewave				
<b>BATTERY</b>					
Battery Type & Number	12V / 7Ah x 1	12V / 9Ah x 1	12V / 7Ah x 2	12V / 9Ah x 2	12V / 9Ah x 2
Typical Recharge Time	4 hours recover to 90% capacity		4-6 hours recover to 90% capacity		
<b>INDICATORS</b>					
AC Mode	Green lighting		Green lighting		Green lighting
Battery Mode	Green flashing		Yellow flashing		Yellow flashing
Fault	N/A		Red lighting		Red lighting
<b>ALARM</b>					
Battery Mode	Beeps every 10 seconds				
Low Battery	Beeps every second				
Overload	Beeps every 0.5 second				
Fault	Continuously beeping				
<b>PROTECTION</b>					
Full Protection	Overload, discharge and overcharge protection				
<b>PHYSICAL</b>					
Dimension, D X W X H (mm)	279 x 101 x 142			320 x 130 x 182	
Net Weight (kgs)	4.25	4.9	8.2	10.4	11
<b>ENVIRONMENT</b>					
Humidity	0-90% RH @ 0- 40°C (non-condensing)				
Noise Level	Less than 40dB				
<b>BACKUP TIME</b>					
Battery Config.	7.0Ah x 1	9.0Ah x 1	7.0Ah x 2	9.0Ah x 2	9.0Ah x 2
Backup time	19 mins	20 mins	18 mins	18 mins	15 mins
Load Condition	Mac book 15" (90W)*1	Mac book 13" (60W)*2	Mac book 13" (60W)*1 Mac book 15" (90W)*1	Mac book 13" (60W)*2 Mac book 15" (90W)*1	Mac book 13" (60W)*2 Mac book 15" (90W)*2

\* Product specifications are subject to change without further notice

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda FSP, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/fsp-fp-800-ups-uredjaj-akcija-cena/>