

## Informacije o proizvodu (EN)

GEMBIRD EG-UPS-031 - 2400 UPS uređaj



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/gembird-eg-ups-031-2400-ups-uredjaj-akcija-cena/>

# UPS with LCD display, 650 VA, black

EG-UPS-031

## ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



## Features

- Uninterruptable 650 VA power supply with modified sine wave output
- Automatic AC voltage regulation (AVR)
- Intelligent surge-, overload and short-circuit protection
- Audible and visual alarms
- LCD status display
- Intelligent battery management with overcharge and over-discharge protection

## Packaging

Q'ty in crtn, pcs	3
Crtn volume, CUM	0.04158
Crtn weight, kgs	17.08
Individual package size LxWxH:	375x150x230 mm
Carton size LxWxH:	450x385x240 mm
Country of origin	CN
Barcode	8716309080835
Customs code	8504408590

## Package contents

- UPS
- Power cord
- Spare fuses
- User manual

## Certificates



## Specifications

Type: line interactive  
 Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC  $\pm$  25%, 50 / 60 Hz  $\pm$  10%  
 Output: 220 V AC  $\pm$  10%, 50 / 60 Hz  $\pm$  1% (220 V AC  $\pm$  5 % at inverter mode)

Switching time about or less than 8 ms  
 Backup time: 8...20 mins (depends on the load)  
 Battery: sealed lead-acid 12 V DC / 7Ah  
 Charge time: up to 12 hours  
 Output sockets: 2 pcs x C13, 1 pc x german Shuko  
 Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 650 VA (390 W)  
 Charging current: up to 1.2 A  
 Noise: < 45 dB at 1 m distance  
 Dimensions: 340 x 95 x 165 mm  
 Product weight: 5.2 kg  
 "Cold-start" function

## System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Gembird, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/gembird-eg-ups-031-2400-ups-uredjaj-akcija-cena/>