

Informacije o proizvodu (EN)

GEMBIRD EG-UPS-035 2000VA 1200W UPS uređaj



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/gembird-eg-ups-035-2000va-1200w-ups-uredjaj-akcija-cena/>

UPS with USB and LCD display, 2000 VA, black

EG-UPS-035

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable 2000 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Packaging

Q'ty in crtn, pcs	2
Crtn volume, CUM	0.05421375
Crtn weight, kgs	27.3
Individual package size LxWxH:	450x300x180 mm
Carton size LxWxH:	450x395x305 mm
Country of origin	CN
Barcode	8716309116602
Customs code	8504408590

Package contents

- UPS
- Power cord
- USB cable
- Software CD
- Spare fuse

Certificates



Specifications

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC \pm 25% (162-295V), 50 / 60 Hz \pm 10%

Output: 220 V AC \pm 10%, 50 / 60 Hz \pm 1% (220 V AC \pm 10 % at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 9 Ah x 2 pcs (connected in series)

Charge time: up to 90% after 6-8 hours

Sockets: built-in input cable, 3 pcs x C13 output, 2 pcs x german Shuko output

Interface communication: USB-BF socket, RJ45

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 2000 VA (1200 W)

Charging current: 0.5 A (default)

Noise: < 45 dB at 1 m distance

Dimensions: 125 ? 380 ? 225 mm

Net weight: 12.9 kg

"Cold-start" function

System requirements

Software is compatible with Windows Vista, Windows 7/8, Windows 2008 server

In order to work correctly, the connected load should be at least 5% of the

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Gembird, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/gembird-eg-ups-035-2000va-1200w-ups-uredjaj-akcija-cena/>