

Informacije o proizvodu (EN)

GEMBIRD EG-UPS-PS2000-01 2000VA UPS uređaj



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/gembird-eg-ups-ps2000-01-2000va-ups-uredjaj-akcija-cena/>

2000VA pure sine wave UPS, LCD display, USB, black

EG-UPS-PS2000-01

ULTIMATE DEFENCE

- Pure sine wave output
- Provide backup power Prevents data loss
- Protects your sensitive and valuable equipment
- Perfect support for solar panel installations and other sensitive equipment that requires pure sinewave input
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable power supply with pure sine wave output
- USB interface
- Automatic AC voltage regulation (AVR)
- Intelligent overload and short-circuit protection
- Audible and visual alarms
- LCD display and LED status indication
- Internal battery with overcharge and over-discharge protection

Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.04125
Crtn weight, kgs	21
Individual package size LxWxH:	492x316x236 mm
Carton size LxWxH:	500x250x330 mm
Country of origin	CN
Barcode	8716309087353
Customs code	8504408590

Package contents

- UPS
- Power cord
- Spare fuse

Certificates



Specifications

Type: line interactive

Waveform: sine, 5% distortion at linear load, PF > 0.8 (on battery)

Input: AC 220V±25%, 50Hz/60Hz ±10%

Output: AC 220V±12%, 50Hz/60Hz ±1% (AC 220V±5% at inverter mode)

Switching time: u to 10 ms

Backup time: 10...30 mins (depends on the load)

Battery: 151 x 65 x 94 mm, sealed lead-acid 12V/9Ah, F2 terminals x 3 pcs

Charge time: up to 12 hours

Sockets: C14 input, 4 outputs x C13; USB-BF connector

Operating conditions: 0°C-40°C, at humidity 10-90%RH non condensing

Power: 2000VA (1600 W)

Charging current: up to 1.2 A

Noise: < 50 dB at 1 m distance

Dimensions: 412 x 215 x 144 mm

Product weight: 18.5 kg

"Cold-start" function

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Gembird, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/gembird-eg-ups-ps2000-01-2000va-ups-uredjaj-akcija-cena/>