

Informacije o proizvodu (EN)

LEGRAND Keor SP 1500VA UPS uređaj



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/legrand-keor-sp-1500va-ups-uredjaj-akcija-cena/>

Keor SP 1000 VA
Keor SP 1500 VA
Keor SP 2000 VA

3 101 86 – 3 101 87 – 3 101 88 – 3 109 64
3 101 89 – 3 101 90 – 3 101 91 – 3 110 48
3 101 92 – 3 101 93 – 3 101 94 – 3 110 49



TABLE OF CONTENTS

Page

| | |
|-----------------------------|---|
| 1. General features..... | 1 |
| 2. Technical features | 1 |

1. GENERAL FEATURES

The Legrand UPS Keor SP 1000/1500/2000 VA models are uninterruptible power sources with interactive line technology. They deliver an active power of 600, 900 and 1200 W, they are CPU-controlled and are equipped, internally, with valve-regulated, hermetically sealed lead accumulator batteries to guarantee a minimum backup time of 5 minutes at 80% of the load.

The presence of an electronic stabilizer (AVR) inside the UPS provides the connected loads with effective protection against any interference in the electrical mains.

This UPS is available with different types of output sockets:

- Versions 3 101 86/3 101 89/3 101 92: six IEC output sockets
- Versions 3 101 87/3 101 90/3 101 93: two standard German plus two IEC sockets
- Versions 3 101 88/3 101 91/3 101 94: two standard French plus two IEC sockets
- Versions 3 109 64/3 110 48/3 110 49: six IEC output sockets with British Standard Input Power Plug

The UPS is equipped with an USB charging port for mobile devices.

The UPS can be connected to a PC through the USB/RS232 port allowing you to monitor its operations, thanks to the free software, and carry out an emergency shutdown of Windows and Linux operating systems.

Keor SP is managed by a microprocessor and is able to display the following alarms and operating modes through the smart LED bar:

- normal operation
- battery-powered operation
- overload
- generic fault
- backup time
- end of backup time

The Keor SP is CE marked and compliant with EU directives 2014/30 and 2014/35.

It's also designed and built in compliance with the following standards:

- EN 62040-1 "Safety requirements for UPSs"
- EN 62040-2 "Electromagnetic Compatibility requirements (EMC) for UPSs"

2. TECHNICAL FEATURES

| Model | SP 1000 | SP 1500 | SP 2000 |
|-------|---------|---------|---------|
|-------|---------|---------|---------|

| General features | | | |
|--------------------|---------------------|------|------|
| Nominal power (VA) | 1000 | 1500 | 2000 |
| Active power (W) | 600 | 900 | 1200 |
| Technology | Line interactive VI | | |
| Waveform | Simulated sinewave | | |

| Input | |
|---------------------|---------------|
| Nominal voltage (V) | 230 |
| Voltage range (V) | 170 - 290 |
| Frequency (Hz) | 50 - 60 ± 5Hz |

| Output | |
|-----------------------|----------------------------|
| Outlets type: | Backup: 6°C13 |
| - IEC Version | Backup: 2°C EE 7/3 + 2°C13 |
| - German Version | Backup: 2°C EE 7/5 + 2°C13 |
| - French Version | Backup: 2°C EE 7/5 + 2°C13 |
| USB charger / Voltage | Type A / 5 V |
| Voltage (V) | 230 ± 10% |
| Frequency (Hz) | 50 - 60 ± 1Hz |

| Protections | | | |
|-----------------|---------------------------------------------------------------------|------|------|
| Full protection | Overload, short circuit, discharge, overcharge and surge protection | | |
| Type | Fuse | | |
| Surgerating | 312J | 312J | 312J |

| Batteries | | | |
|-----------------------------|----------|----------|----------|
| Number of batteries | 2 | | |
| Battery series Type/Voltage | VRLA 7Ah | VRLA 9Ah | VRLA 9Ah |

| Communication and Management | |
|------------------------------|------------------------------------|
| Interface | RGB LED bar (green / orange / red) |
| Remote Management | USB HID (Type B), RS232 |
| Alarms | Visual (LED bar), Audible (buzzer) |
| NAS Compatibility | YES |

| Mechanical Features | | | |
|-----------------------------|-----------------|-----|------|
| Measurements W x D x H (mm) | 148 x 380 x 173 | | |
| Net Weight (kg) | 8,6 | 9,6 | 10,3 |

| Environmental Conditions | |
|----------------------------|---------------------------|
| Operating temperature (°C) | 0 - 40 |
| Relative humidity (%) | < 95 (without condensing) |
| Noise level (dB) | ≤ 40 |

| Certifications | |
|---------------------|----------------------------|
| Standards and marks | EN 62040-1, EN 62040-2, CE |

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Legrand, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/legrand-keor-sp-1500va-ups-uredjaj-akcija-cena/>