

Informacije o proizvodu (EN)

STIEBEL ELTRON protočni bojler EIL 7 Plus

STIEBEL ELTRON



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/stiebel-eltron-protocni-bojler-eil-7-plus-akcija-cena/>

EIL 7 Plus

MINI INSTANTANEOUS WATER HEATERS

PRODUCT-NO.: 200141

The fastest way to enjoy hot water Discover all the options Are there places in your home where you only need hot water occasionally? Then this mini instantaneous water heater is the right solution for you. The water quickly gets up to temperature thanks to decentralised installation.

The main features

Suitable for undersink installation

Can be operated with pressure-tested or non-pressurised taps

Special aerator for perfect flow pattern

Mini instantaneous water heater with hydraulic control for small amounts of hot water available immediately



EIL 3 Plus

Product-No.: 200138



EIL 4 Plus

Product-No.: 200139



EIL 6 Plus

Product-No.: 200140



Type	EIL 3 Plus	EIL 4 Plus	EIL 6 Plus
Part no.	200138	200139	200140

Technical data

Rated voltage	230 V	230 V	230 V
Rated voltage 1	200 V	200 V	200 V
Rated voltage 2	220 V	220 V	220 V
Rated voltage 3	230 V	230 V	230 V
Rated output	3,53 kW	4,4 kW	5,7 kW
Rated output 1	2,7 kW	3,3 kW	4,3 kW
Rated output 2	3,2 kW	4,0 kW	5,2 kW
Rated output 3	3,53 kW	4,4 kW	5,7 kW
Rated current	15,2 A	19,1 A	24,7 A
Rated current 1	13,3 A	16,7 A	21,6 A
Rated current 2	14,5 A	18,2 A	23,6 A
Rated current 3	15,2 A	19,1 A	24,7 A
Fuse protection	16 A	20 A	25 A
Fuse protection 1	16 A	20 A	25 A
Fuse protection 2	16 A	20 A	25 A
Fuse protection 3	16 A	20 A	25 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 3	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE

Conductivity $\sigma_{15} \leq$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25\text{ }^\circ\text{C}$)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25\text{ }^\circ\text{C}$)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Resistivity $\rho_{15} \geq$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25\text{ }^\circ\text{C}$)	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25\text{ }^\circ\text{C}$)	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Height	143 mm	143 mm	143 mm
Width	190 mm	190 mm	190 mm
Depth	82 mm	82 mm	82 mm
Water connection	G 3/8 A	G 3/8 A	G 3/8 A
ON	> 1,6 l/min	> 2,0 l/min	> 2,6 l/min
IP rating	IP25	IP25	IP25
Colour	white	white	white
Weight	1.40 kg	1.40 kg	1.40 kg
Energy efficiency class	A	A	A



Type	EIL 7 Plus
Part no.	200141

Technical data

Rated voltage	400 V
Rated voltage 1	380 V
Rated voltage 2	400 V
Rated voltage 3	415 V
Rated output	6,5 kW
Rated output 1	5,9 kW
Rated output 2	6,5 kW
Rated output 3	7,0 kW
Rated current	16,3 A
Rated current 1	15,5 A
Rated current 2	16,3 A
Rated current 3	16,9 A
Fuse protection	20 A
Fuse protection 1	16 A
Fuse protection 2	20 A
Fuse protection 3	20 A
Frequency	50 Hz
Frequency 1	50/60 Hz
Frequency 2	50/60 Hz
Frequency 3	50/- Hz
Phases	2/PE

Conductivity $\sigma_{15} \leq$	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25\text{ }^\circ\text{C}$)	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25\text{ }^\circ\text{C}$)	909 $\mu\text{S}/\text{cm}$
Resistivity $\rho_{15} \geq$	1100 $\Omega\text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25\text{ }^\circ\text{C}$)	1100 $\Omega\text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25\text{ }^\circ\text{C}$)	1100 $\Omega\text{ cm}$
Height	143 mm
Width	190 mm
Depth	82 mm
Water connection	G 3/8 A
ON	>2,6 l/min
IP rating	IP25
Colour	white
Weight	1.40 kg
Energy efficiency class	A

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Stiebel Eltron, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/stiebel-eltron-protocni-bojler-eil-7-plus-akcija-cena/>