

## Informacije o proizvodu (EN)

D-LINK DGS-108 switch

The D-Link logo is displayed in a bold, teal-colored font.

Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/d-link-dgs-108-switch-akcija-cena/>

## Product Highlights

### High-Speed Networking

Up to five or eight Gigabit Ethernet ports can be used to connect high-speed devices, allowing fast file transfers and maximising network bandwidth

### Quality of Service

Layer 2 Quality of Service (QoS) provides traffic prioritisation on the local network, ensuring smooth VoIP calls and responsive applications

### Environmentally Friendly

IEEE 802.3az Energy-Efficient Ethernet (EEE) reduces power consumption when ports are not in use, conserving energy and lowering costs



## DGS-105/108

# 5/8-Port Gigabit Unmanaged Desktop Switch

## Features

### Fast Connectivity

- Five (DGS-105) or eight (DGS-108) Gigabit LAN ports for high-speed wired connections
- Plug-and-play installation for convenience
- Cable diagnostics notifies users of cable conditions through diagnostic LEDs

### Multicast Features

- L2 multicast functions including IGMP snooping optimise multicast data streams for bandwidth intense applications like IPTV.

### Robust Design

- Rugged metal housing

### Green Ethernet Features

- Reduces power on a port when no link is detected
- Adjusts power on a port by detecting the length of the connected cable

### Eco-Friendly Design

- Energy Star compliant
- RoHS compliant

The DGS-105/108 5/8-Port Gigabit Unmanaged Desktop Switch are ideally suited for Small Office Home Office (SOHO), Small Medium Business (SMB), and Small Medium Enterprise (SME) environments. With a durable design, silent operation, and plug-and-play functionality, the DGS-105/108 switches can be easily set up and be placed in almost any location where network connectivity is required. Support for IEEE 802.3az Energy-Efficient Ethernet (EEE), Layer 2 Quality of Service (QoS), and Gigabit Ethernet connection speeds provide advanced features in a compact package.

## Robust Design

The DGS-105/108 are designed with durability and performance in mind. Their sturdy metal housing ensures the product can withstand extreme temperatures and can be placed in typical industrial environments such as factories, construction and mining. They help to dissipate heat and reduce stress on internal components.

## Integrated Networking

The DGS-105/108 switches use auto-sensing 10/100/1000 Mbps ports, allowing a small workgroup to flexibly connect Ethernet, Fast Ethernet, and Gigabit devices to create an integrated network. These ports detect the network speed and auto-negotiate between 10BASE-T and 100BASE-TX at full and half-duplex, and 1000BASE-TX at full duplex, allowing you to get the maximum speed possible for each device connected to your network.

## Simplified Installation

All of the ports on the DGS-105/108 switches support automatic MDI/MDIX crossover, eliminating the need for crossover cables or uplink ports. Each port can be plugged in directly to a server, hub, router, or switch using regular straight-through twisted-pair Ethernet cables. In addition, the DGS-105/108 switches feature multiple front-facing, easy-to-access Ethernet ports with two colour LED indicators per port to easily distinguish link status.

### 5/8-Port Gigabit Unmanaged Desktop Switch

#### Green Technology

The DGS-105/108 switches feature green technology, such as IEEE 802.3az Energy-Efficient Ethernet (EEE), link status detection, and cable length detection. Energy-Efficient Ethernet reduces power consumption of the switch when network utilisation is low, reducing the cost of ownership during periods of inactivity. Link status detection automatically powers down ports when there is no link detected, saving power when the connected device has been shut down or disconnected. Cable length detection automatically adjusts the power output of the port based on the length of the cable, reducing the power requirements of the switch to only what is necessary for the installation.

#### Traffic Management

The DGS-105/108 switches include traffic management features, such as IEEE 802.1p Quality of Service (QoS) and IEEE 802.3x Flow Control. The 802.1p QoS feature allows traffic to be classified in 8 priority levels, allowing different types of traffic to be prioritised, depending on their importance. Flow Control signals to clients when the switch's input buffer is full, helping to minimise dropped packets and providing a more reliable connection for all of your connected devices.

#### Technical Specifications

##### General

Model Number	• DGS-105	• DGS-108
Device Interfaces	• 5 10/100/1000BASE-T ports	• 8 10/100/1000BASE-T ports
Standards	<ul style="list-style-type: none"> <li>• IEEE 802.3 10BASE-T</li> <li>• IEEE 802.3u 100BASE-TX</li> <li>• IEEE 802.3ab 1000BASE-T</li> <li>• IEEE 802.3x Flow Control                             <ul style="list-style-type: none"> <li>• IEEE 802.1p QoS</li> </ul> </li> <li>• IEEE 802.3az Energy-Efficient Ethernet (EEE)</li> </ul>	
Media Interface Exchange	• Auto MDI/MDIX adjustment for all ports	

##### Performance

Transmission Method	• Store-and-forward	
Data Transfer Rates	<ul style="list-style-type: none"> <li>• Ethernet:                             <ul style="list-style-type: none"> <li>• 10 Mbps (half-duplex)</li> <li>• 20 Mbps (full-duplex)</li> </ul> </li> <li>• Fast Ethernet:                             <ul style="list-style-type: none"> <li>• 100 Mbps (half-duplex)</li> <li>• 200 Mbps (full-duplex)</li> </ul> </li> <li>• Gigabit Ethernet:                             <ul style="list-style-type: none"> <li>• 2000 Mbps (full-duplex)</li> </ul> </li> </ul>	
Packet Filtering/Forwarding Rates	<ul style="list-style-type: none"> <li>• Ethernet: 14,880 pps per port</li> <li>• Fast Ethernet: 148,800 pps per port</li> <li>• Gigabit Ethernet: 1,488,000 pps per port</li> </ul>	
MAC Address Table	• 2K entries	• 4K entries
MAC Address Learning	• Automatic update	
RAM Buffer	• 128 KB	• 192 KB

##### LEDs

Power (per unit)	✓
Link/Activity/Speed (per port)	✓

# DGS-105/108 5/8-Port Gigabit Unmanaged Desktop Switch

Physical		
Dimensions	• 100 x 98 x 28 mm (3.93 x 3.86 x 1.10 inches)	• 162 x 102 x 28 mm (3.54 x 2.83 x 1.06 inches)
Weight	• 267 grams (0.59 lbs)	• 415 grams (0.92 lbs)
Power	• 5 V/1 A	
Power Consumption	<ul style="list-style-type: none"> <li>Powered on (standby):                             <ul style="list-style-type: none"> <li>DC input: 0.3 W</li> <li>AC input: 0.3 W</li> </ul> </li> <li>Maximum:                             <ul style="list-style-type: none"> <li>DC input: 1.85 W</li> <li>AC input: 3.10 W</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Powered on (standby):                             <ul style="list-style-type: none"> <li>DC input: 0.4 W</li> <li>AC input: 0.4 W</li> </ul> </li> <li>Maximum:                             <ul style="list-style-type: none"> <li>DC input: 3.05 W</li> <li>AC input: 4.62 W</li> </ul> </li> </ul>
Temperature	<ul style="list-style-type: none"> <li>Operating: 0 to 45 °C (32 to 104 °F)</li> <li>Storage: -10 to 70 °C (14 to 158 °F)</li> </ul>	
Humidity	<ul style="list-style-type: none"> <li>Operating: 0% to 95% non-condensing</li> <li>Storage: 0% to 95% non-condensing</li> </ul>	
MTBF	• 604,194 hours	• 621,163 hours
Heat Dissipation	• Maximum: 6.31 BTU/h	• Maximum: 10.40 BTU/h
Certifications		
Safety	<ul style="list-style-type: none"> <li>cUL</li> <li>CB</li> <li>LVD</li> </ul>	<ul style="list-style-type: none"> <li>CCC</li> <li>BSMI</li> </ul>
EMI/EMC	<ul style="list-style-type: none"> <li>FCC Class B</li> <li>CE Class B</li> <li>ICES-003 Class B</li> </ul>	<ul style="list-style-type: none"> <li>RCM</li> <li>CCC</li> <li>BSMI</li> </ul>
Software Features		
L2 Features	• IGMP Snooping	



For more information: [www.dlink.com](http://www.dlink.com)

**D-Link European Headquarters.** D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2018 D-Link Corporation. All rights reserved. E&OE.

Updated June 2018

**D-Link®**

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda D-Link, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/d-link-dgs-108-switch-akcija-cena/>