

## Informacije o proizvodu (EN)

INTELLINET 24-Port 561044 switch



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/intellinet-24-port-561044-switch-akcija-cena/>



## 24-Port Gigabit Ethernet Switch with 2 SFP Ports

24 x 10/100/1000 Mbps RJ45 Ports + 2 x SFP, IEEE 802.3az (Energy Efficient Ethernet), 19" Rackmount, Metal

Part No.: **561044**

EAN-13: 0766623561044 | UPC: 766623561044

---

### Boost your network speed

The Intellinet Network Solutions Gigabit Ethernet Rackmount Switch, model 561044, offers an array of features while providing superior network throughput.

### Extreme Flexibility

Twenty-four 10/100/1000 Mbps auto-sensing ports automatically detect optimal network speeds.

### Eliminate Bottlenecks with 26 Gigabit Ports

Equipped with 24 auto-sensing 10/100/1000 Mbps RJ45 Gigabit Ethernet ports, this switch offers plenty of performance for your computers, servers and other networking devices. In addition, two small form-factor pluggable GBIC module slots (SFP) provide fiber connectivity for greater distances. These are not shared combo-ports, but true Gigabit ports, pushing the total available bandwidth up to 52 Gbps.

### Features:

- 10/100/1000 auto-sensing ports automatically detect optimal network speeds
- Two small form-factor pluggable GBIC module slots (SFP)
- All RJ45 ports with Auto-MDIX (auto uplink) support
- Supports NWay auto-negotiation

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Store and forward switching architecture
- Full/half duplex operation
- Complies with the IEEE 802.3az (Energy Efficient Ethernet EEE) specification
- Green Ethernet power-saving technology deactivates unused ports and adjusts power levels based on the cable length
- Supports 802.3x flow control for full duplex mode and collision-based backpressure for half duplex mode
- 52 Gbps switch fabric
- Supports Jumbo frames 9 kBytes
- 512 kBytes buffer memory
- Supports up to 8K MAC address entries
- Fanless design ideal for silent operation
- Includes 19" rackmount brackets
- Supports MAC address auto-learning and auto-aging
- Fully NDAA-compliant
- Three-Year Warranty

## Specifications:

### Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Twisted Pair Gigabit Ethernet)
- IEEE 802.3az (Energy Efficient Ethernet EEE)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (flow control, for full duplex mode)

### General

- Media support:
  - 10Base-T Cat3, 4, 5 UTP/STP RJ45
  - 100Base-TX Cat5 UTP/STP RJ45
  - 1000Base-T Cat5e UTP/STP RJ45
- Packet filter/forwarding rate:
  - 1,488,000 pps (1000 Mbps)
  - 148,800 pps (100 Mbps)
  - 14,880 pps (10 Mbps)
- Buffer memory: 512 kBytes
- MAC address table: 8K entries
- Backplane speed: 52 Gbps
- Switch architecture: store and forward
- 24 RJ45 Gigabit Ethernet ports
- 2 SFP (Small Formfactor Pluggable) slots
- Certifications: FCC Class A, CE, UKCA, NDAA

### LEDs

- Power
- Link Speed per port: 1000 Mbps

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Link/Activity per port

#### Power

- Internal power supply, 100 – 240 VAC, 50/60 Hz
- Power consumption: 20 watts (maximum)

#### Environmental

- Metal housing, 19" rackmount, 1 U
- Dimensions: 440 (W) x 208 (L) x 44 (H) [mm] / 17.32 (W) x 8.19 (L) x 1.73 (H) [in.]
- Weight: 3.00 kg (6.6 lbs.)
- Operating temperature: 0 – 40°C (32 – 104°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -10 – 70°C (14 – 158°F)

#### Package Contents

- Gigabit Ethernet Rackmount Switch
- Power cable
- 19" rackmount brackets
- User manual





Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Intellinet, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/intellinet-24-port-561044-switch-akcija-cena/>