

Informacije o proizvodu (EN)

SEAGATE hard disk 1TB ST1000DM014 Barracuda



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/seagate-hard-disk-1tb-st1000dm014-barracuda-akcija-cena/>



3.5 HDD DATA SHEET

Amazing Versatility. Unmatched Dependability.



Seagate brings over 20 years of trusted performance and reliability to the Seagate® BarraCuda® 3.5-inch HDD—now available in capacities up to 8TB.



Best-Fit Applications

- Desktop or all-in-one PCs
- Home servers
- Entry-level direct-attached storage devices (DAS)

Key Advantages

Versatile HDDs for all your PC needs bring you industry-leading excellence in personal computing.

For over 20 years the BarraCuda family has delivered super-reliable storage for the hard drive industry. **Capacities up to 8TB** for desktops, BarraCuda leads the market with the widest range of storage options available.

Advanced Power modes help save energy without sacrificing performance.¹

SATA 6Gb/s interface optimizes burst performance.¹

¹ Performance may vary depending on user's hardware configuration and operating system.



Specifications	8TB	6TB	4TB	3TB
Standard Model Number	ST8000DM004	ST6000DM003	ST4000DM004	ST3000DM007
Bytes per Sector	4096	4096	4096	4096
Performance				
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max Sustained Data Rate, OD Read (MB/s)	190MB/s	185MB/s	190MB/s	185MB/s
Cache, Multisegmented (MB)	256MB	256MB	256MB	256MB
Rotational Speed (RPM)	5400RPM	5400RPM	5400RPM	5400RPM
Recording Technology	SMR	SMR	SMR	SMR
Reliability/Data Integrity				
Load/Unload Cycles	600,000	600,000	600,000	600,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Power-On Hours (per year)	2400	2400	2400	2400
Workload Rate Limit (TB/Year)	55	55	55	55
Warranty, Limited (years)	2	2	2	2
Power Management				
Startup Power (A)	2.0A	2.0A	2.0A	2.0A
Operating Mode, Typical (W)	5.3	5.3	3.7	3.7
Idle Average (W)	3.4W	3.4W	2.5W	2.5W
Standby Mode/Sleep Mode, Typical (W)	0.25/0.25	0.25/0.25	0.25/0.25	0.25/0.25
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%
Environmental/Temperature				
Operating (ambient, min)	0°C	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C	60°C
Nonoperating (ambient)	-40°C - 70°C	-40°C - 70°C	-40°C - 70°C	-40°C - 70°C
Halogen Free	Yes	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes	Yes
Physical				
Height (mm/in, max)	26.11mm/1.028in	26.11mm/1.028in	20.20mm/0.795in	20.20mm/0.795in
Width (mm/in, max)	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	630g/1.389lb	610g/1.345lb	490g/1.08lb	490g/1.08lb
Carton Unit Quantity	20	20	25	25
Cartons per Pallet/Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8



Specifications	2TB		1TB	
Standard Model Number	ST2000DM005	ST2000DM008	ST1000DM010	ST1000DM014
Bytes per Sector	4096	4096	4096	4096
Performance				
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max Sustained Data Rate, OD Read (MB/s)	190MB/s	220MB/s	210MB/s	220MB/s
Cache, Multisegmented (MB)	256MB	256MB	64MB	256MB
Rotational Speed (RPM)	5400RPM	7200RPM	7200RPM	7200RPM
Recording Technology	SMR	SMR	CMR	SMR
Reliability/Data Integrity				
Load/Unload Cycles	600,000	600,000	50,000	600,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Power-On Hours (per year)	2400	2400	2400	2400
Workload Rate Limit (TB/Year)	55	55	55	55
Warranty, Limited (years)	2	2	2	2
Power Management				
Startup Power (A)	2.0A	2.0A	2.0A	2.0A
Operating Mode, Typical (W)	3.7	5.1	5.3	5.1
Idle Average (W)	2.5W	3.9W	4.60W	3.9W
Standby Mode/Sleep Mode, Typical (W)	0.25/0.25	0.3/0.3	0.94/0.94	0.3/0.3
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%
Environmental/Temperature				
Operating (ambient, min)	0°C	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C	60°C
Nonoperating (ambient)	-40°C - 70°C	-40°C - 70°C	-40°C - 70°C	-40°C - 70°C
Halogen Free	Yes	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes	Yes
Physical				
Height (mm/in, max)	20.20mm/0.795in	20.20mm/0.795in	19.99mm/0.787in	20.20mm/0.795in
Width (mm/in, max)	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	490g/1.08lb	490g/1.08lb	400g/0.88lb	490g/1.08lb
Carton Unit Quantity	25	25	25	25
Cartons per Pallet/Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Seagate, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/seagate-hard-disk-1tb-st1000dm014-barracuda-akcija-cena/>