

Informacije o proizvodu (EN)

CHIEFTEC napajanje Polaris 3.0 PPS-1250FC-A3



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/chiefttec-napajanje-polaris-30-pps-1250fc-a3-akcija-cena/>

- ATX 3.0 with PCIe GEN5
- 80PLUS® GOLD certified efficiency
- Japanese Main Capacitors
- LLC Half-Bridge converter with DC to DC technology
- Fully modular cable management

The **CHIEFTEC Polaris 3.0 series** is designed to **Intel's ATX 3.0** standard and supports **PCIe GEN 5** with **80 PLUS® GOLD** certified efficiency, promising exceptional performance. Polaris 3.0 features state-of-the-art technical design including **LLC half-bridge converter with DC-to-DC technology**, as well as **Japanese main capacitors** to achieve low ripple and tight voltage regulation.

The **Polaris 3.0** 135mm FDB silent fan optimizes the balance between cooling and noise with excellent durability. **Fully modular cable management** ensures a clean and convenient build inside any system.






TECHNICAL DATA	
Model	Polaris 3.0 1250W
Articel no.	PPS-1250FC-A3
Specification	ATX 12V 3.0
Form factor	ATX
Efficiency	80 PLUS® GOLD
PFC	Active PFC (0.9)
Fan	135mm FDB fan
Dimension (DxWxH)	160mm x 150mm x 86mm
Security	AFC (Automatic Fan speed Control) OPP (Overload protection) OTP (Over Temperature Protection) OVP (Overvoltage protection) SCP (Short-circuit protection) SIP (Surge & Inrush Protection) UVP (Under Voltage protection) OCP (Over-Current Protection)
Warranty	5 Years

OUTPUT DATA						
PPS-1250FC-A3	AC Input	100-240V~ / 15-8A / 50 - 60Hz				
	DC Output	+3.3V	+5V	+12V	-12V	+5VSB
	Max. Current	22A	22A	104.1A	0.3A	3.0A
	Max. Combined Power	120W		1250W	3.6W	15W
		1250W				

*The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

	Cable	Connectors	Length (mm)
	20+4 PIN ATX	1	650
	8 PIN EPS (4+4)	2	2 x 650
	8 PIN PCIe (6+2)	4	2 x 600/100
	16 PIN PCIe GEN5	1	600
	SATA	12	3 x 550/100/100/100
	MOLEX	4	550/100/100/100

Certification



Version: 01/2023

*The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Chieftec, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/chieftec-napajanje-polaris-30-pps-1250fc-a3-akcija-cena/>