

## Informacije o proizvodu (EN)

TESLA inverter klima TA35MMFT-1232IHWT

TESLA



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/tesla-inverter-klima-ta35mmft-1232ihwt-akcija-cena/>



## A+++

When choosing an AC, it is important to think about energy saving. Most wall-mounted AC models are classified as A+ or higher, while the most energy-efficient units boast the highest energy class (A+++).



### ODU HEATER

Adding a heater to the outdoor unit can help melt ice and snow in the winter, and prevent the outdoor fan from blocking, thus ensuring optimal performance when the machine is in heating mode.



### NIGHT MODE

When this mode is activated, the AC can increase or decrease the temperature by 1°C per hour during the first three hours. It allows the unit to operate in a more energy-efficient and quiet manner during nighttime.



### UV LAMP

UV light is used in ACs to kill or inactivate microorganisms such as bacteria, viruses, and mold. UV lamp is installed inside the device, where it emits UV-C light to clean the air as it passes through the unit.



### -25 DEGREES

Thanks to its great technical characteristics, selected Tesla AC models ensure smooth operation in temperatures as low as -25°C, providing users with a stable performance in all seasons.



### 3D AIRFLOW

Depending on the model, you can choose between different air dispersion positions available, such as blanket-style, shower-style, breeze etc.



## Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi

<b>Capacity</b>			12000BTU	
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ	
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity</b>		W	3500(650-4100)                      4200(930-4200)	
<b>Power input</b>		W	870(130-1550)                      1060(230-1300)	
<b>Current input</b>		A	4.2(0.56-5.8)                      4.8(1.0-6.3)	
<b>SEER / Energy Class</b>			8,7/A+++                      /	
<b>SCOP / Energy Class - average</b>			/                      4,7/A++	
<b>SCOP / Energy Class - warmer</b>			/                      5,5/A+++	
<b>Operating range (°C)</b>		°C	16-49                      -25-30	
<b>Energy consumption (per year, based on standard test results)</b>		kWh	145                      /	
<b>Energy consumption (per year, based on standard test results) - average</b>		kWh	/                      853	
<b>Energy consumption (per year, based on standard test results) - warmer</b>		kWh	/                      866	
<b>Dehumidifying</b>		Kg/h	1,7	
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX0/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I	
<b>Max. input consumption</b>		W	1500	
<b>Max. current</b>		A	9	
<b>Compressor</b>		Model	KSN98D66UER3	
		Type	Rotary	
		Brand	GMCC	
<b>Indoor</b>	Indoor Air Circulation	m <sup>3</sup> /h	650	
	Indoor Noise Level dB	dB(A)	31/44/47/50/56	
	Net Dimension	mm	827×299×201	
	Packing Dimension	mm	891×371×282	
	Net Weight / Gross Weight	Kg	8,5/11,5	
<b>Outdoor</b>	Outdoor Noise Level dB	dB(A)	62	
	Net Dimension	mm	705×530×280	
	Packing Dimension	mm	825×595×345	
	Net Weight / Gross Weight	Kg	24,5/27	
	Refrigerant Type		R32	
	Refrigerant Weight	Kg	0,6	
	GWP		675	
	tCO <sub>2</sub> eq.		0,41	
<b>Max. Discharge / Max. Suction pressure</b>		Mpa	4.3/2.5	
<b>Refrigerant piping</b>		Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
		Max. refrigerant pipe length / Max. difference in level	m	25/15

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Tesla, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/tesla-inverter-klima-ta35mmft-1232ihwt-akcija-cena/>