

Informacije o proizvodu (EN)

ENERMAX napajanje ERV1000G-AHG-MAC REVOLUTION III
1000W



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

<https://tehnoteka.rs/p/enermax-napajanje-erv1000g-ahg-mac-revolution-iii-1000w-akcija-cena/>



REVOLUTION III

650W / 750W / 850W / 1000W

REVOLUTION III




- *Integrated with Intel ATX 3.1*
- *Fully Modular 80 PLUS® Gold Certified*
- *Native 12V-2x6 Cable, Providing the GPU with 450-600W Power*
- *Industrial-Grade 100% Japanese Capacitors*
- *Ultra Quiet 120mm FDB Fan*
- *Mesh-sleeved Cables with 16/21 pcs Cable Comb Kit*



Features

- **Compliance with ATX 3.1**
 - Adherence to the latest Intel ATX 3.1 specification.
 - REVOLUTION III 750W / 850W / 1000W models provide one 600W native 12V- 2x6 connector.
 - REVOLUTION III 650W provides one 450W native 12V-2x6 connector.
 - **Excellent Performance Meeting High-end Requirements**
 - 80 PLUS® Gold certified with 93% efficiency at 50% load, which saves more energy and reduces extra heat.
 - Accommodates up to 200% power excursion, catering to high-end GPU requirements.
 - **Silent Operation and Enhanced Durability**
 - Incorporates 100% industrial-grade Japanese capacitors, ensuring top-tier reliability.
 - Equipped with a built-in 120mm FDB fan for ultra quiet operation.
 - **Optimized Safety Design**
 - Optimized safety design, certified for 5000m altitude.
 - Multiple protection circuitries of OCP, OVP, UVP, OPP, SCP, and OTP.
 - **Outstanding User Experience**
 - Modular sockets inclined to one side for better cable managing experience.
 - Mesh-sleeved cables with 21 pcs cable comb kit for 750W / 850W / 1000W models and 16 pcs for 650W model.
 - **Full-Bridge Resonant, High-Efficiency 12V-Centric Power Design**
 - Utilizing active Power Factor Correction (PFC) combined with a full-bridge resonant topology and a 12V synchronous rectification power stage, this design features a high-efficiency single-rail 12V output alongside DC-to-DC converted 3.3V and 5V rails. This architecture significantly increases usable 12V power while effectively improving cross-load regulation across multiple outputs, delivering more stable and cleaner power quality.
 - **Intelligent Fan Technology**
 - Through the Revolution III circuit-based thermal control design, an optimal balance is achieved between component cooling and fan noise, delivering a quiet operating experience.
- * Tested under laboratory conditions.



ATX 3.1 & PCIe 5.1 Ready




Native 12V-2x6 Connector



Ultra Quiet 120mm FDB Fan




Premium Mesh-Sleeved Cables



100% 105°C Japanese Capacitors




Full-Bridge Resonant, High-Efficiency
12V-Centric Power Design



Intelligent Fan Technology

Dimension

Unit : mm



Cables & Connectors

Model	Connectors					
	Mainboard 24P	CPU 4+4P (8P)	12V-2x6 12+4P	PCIe 6+2P (8P)	SATA	4P Molex
650W	1	2	1	2	6	2
750W	1	3	1	3	9	3
850W	1	3	1	3	9	3
1000W	1	2	1	3	9	3

Specifications

General Data								
80 PLUS EFFICIENCY	GOLD							
MODULAR	Fully Modular							
CABLE TYPE	Individually Mesh-Sleeved Cable							
FAN SIZE (MM)	120							
OPERATING TEMPERATURE (°C)	40							
MTBF (HOURS)	>100K							
PROTECTION	OCP, OVP, UVP, OPP, OTP, SCP							
Power Output								
Model	ERV650G-AHG-MAV/C ERV650G-AHG-MAC-W		ERV750G-AHG-MAV/C ERV750G-AHG-MAC-W		ERV850G-AHG-MAV/C ERV850G-AHG-MAC-W		ERV1000G-AHG-MAV/C	
AC Input Voltage	100-240VAC, 50-60Hz						100-240VAC, 50-60Hz 200-240VAC, 50-60Hz (for China only)	
AC Input Current	10-6A						15-8A 8A (for China only)	
DC Output								
	Rated	Combined	Rated	Combined	Rated	Combined	Rated	Combined
+3.3V	20A	100W	20A	100W	20A	100W	20A	100W
+5V	20A		20A		20A		20A	
+12V	54.1A	649.2W	62.4A	748.8W	70.8A	849.6W	83.3A	999.6W
-12V	0.4A	4.8W	0.4A	4.8W	0.4A	4.8W	0.4A	4.8W
+5Vsb	2.5A	12.5W	2.5A	12.5W	2.5A	12.5W	3.0A	15W
Total power	650W		750W		850W		1000W	
Dimensions	140(D) x 150(W) x 86(H) mm							
       								
Barcode								
Model	EAN				UPC			
ERV650G-AHG-MAV/C	4713157728845				819315028841			
ERV650G-AHG-MAC-W	4713157734136				819315020135			
ERV750G-AHG-MAV/C	4713157728869				819315028865			
ERV750G-AHG-MAC-W	4713157734129				819315020128			
ERV850G-AHG-MAV/C	4713157728883				819315028896			
ERV850G-AHG-MAC-W	4713157728821				819315028827			
ERV1000G-AHG-MAV/C	4713157728906				819315028919			
Logistic Information								
Model	ERV650G-AHG-MAV/C ERV650G-AHG-MAC-W		ERV750G-AHG-MAV/C ERV750G-AHG-MAC-W		ERV850G-AHG-MAV/C ERV850G-AHG-MAC-W		ERV1000G-AHG-MAV/C	
Box Dimension	310 x 190 x 110 mm							
Gross Weight / Unit	1.5		1.6		1.6		2.0	
Carton Dimension	640 x 460 x 220 mm							
Q'ty / Carton	8 pcs							
Gross Weight / Carton	19		20		20.2		22.8	

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Enermax, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanесenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

<https://tehnoteka.rs/p/enermax-napajanje-erv1000g-ahg-mac-revolution-iii-1000w-akcija-cena/>